



# Beautiful sparkle, reliable life

## MASTERColour CDM-TD

Range of double-ended, compact, high-efficiency, discharge lamps with a stable colour over lifetime and a crisp, sparkling light

### Benefits

- Stable colour impression over lifetime
- High lamp efficacy results in low operating costs and low heat generation. Provides better operating costs and improved light quality versus standard quartz metal halide (MHN/W-TD)
- Long lamp life compared with incandescent, halogen and quartz metal halide (MHN/W-TD) lamps
- Relatively low heat output enhances comfort for shoppers and staff
- All types are UV-Block for reduced fading risks

### Features

- Warm or cool white colour impression
- Colour rendering good to excellent
- Retrofit in double-ended luminaires for quartz metal halide lamps (MHN/W-TD), thereby allowing to reduce operating costs and improve colour quality
- Burning position horizontal +/-45°

### Application

- Shops and shop windows, offices and public buildings
- Decorative outdoor: floodlighting of facades, statues and monuments

# MASTERCcolour CDM-TD

## Warnings and Safety

- Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures
- Lamps may use electronic or electromagnetic control gear
- Control gear must include end-of-life protection (IEC61167, IEC 62035)
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

## Dimensional drawing



Product	D (max)	D	O	C (max)
MASTERCcolour CDM-TD 70W/830 RX7s 1CT/12	22 mm		8 mm	119.63 mm
MASTERCcolour CDM-TD 150W/942 RX7s 1CT	22 mm		10 mm	137.43 mm
MASTERCcolour CDM-TD 70W/942 RX7s 1CT/12	22 mm	0.75 in	7 mm	119.63 mm
MASTERCcolour CDM-TD 150W/830 RX7s 1CT	22 mm		10 mm	137.43 mm

Controls and dimming	
Dimmable	No
Operating and electrical	
Re-ignition Time (Min) (Max)	15 min
General information	
Cap-Base	RX7S
Life To 10% Failures (Nom)	13000 h
Life To 20% Failures (Nom)	15000 h
Life To 50% Failures (Nom)	16000 h
Life To 5% Failures (Nom)	9000 h
Operating Position	P45
Mechanical and housing	
Bulb Finish	Clear
Bulb Shape	T22

## Approval and application

Order Code	Full Product Name	Energy Consumption kWh/1000 h	Mercury (Hg) Content (Max)	Mercury (Hg) Content (Nom)
928082205125	MASTERCcolour CDM-TD 70W/830 RX7s 1CT/12	71 kWh	3.4 mg	3.4 mg
928084705133	MASTERCcolour CDM-TD 70W/942 RX7s 1CT/12	72 kWh	4.7 mg	4.8 mg
928083605133	MASTERCcolour CDM-TD 150W/830 RX7s 1CT	147 kWh	10.2 mg	10.23 mg
928084805133	MASTERCcolour CDM-TD 150W/942 RX7s 1CT	152 kWh	8.3 mg	8.29 mg

## Operating and electrical (1/2)

Order Code	Full Product Name	Lamp			
		Current (EM) (Nom)	Voltage (Max)	Voltage (Min)	Voltage (Nom)
928082205125	MASTERCcolour CDM-TD 70W/830 RX7s 1CT/12	0.95 A	102 V	86 V	94 V
928084705133	MASTERCcolour CDM-TD 70W/942 RX7s 1CT/12	0.98 A	98 V	82 V	90 V

Order Code	Full Product Name	Lamp			
		Current (EM) (Nom)	Voltage (Max)	Voltage (Min)	Voltage (Nom)
928083605133	MASTERCcolour CDM-TD 150W/830 RX7s 1CT	1.8 A	106 V	90 V	98 V
928084805133	MASTERCcolour CDM-TD 150W/942 RX7s 1CT	1.8 A	110 V	96 V	103 V

# MASTERColour CDM-TD

## Operating and electrical (2/2)

Order Code	Full Product Name	Power (Nom)
928082205125	MASTERColour CDM-TD 70W/830 RX7s 1CT/12	71.0 W
928084705133	MASTERColour CDM-TD 70W/942 RX7s 1CT/12	71.5 W

Order Code	Full Product Name	Power (Nom)
928083605133	MASTERColour CDM-TD 150W/830 RX7s 1CT	147.0 W
928084805133	MASTERColour CDM-TD 150W/942 RX7s 1CT	152.0 W

## Luminaire design requirements

Order Code	Full Product Name	Bulb Temperature (Max)
928082205125	MASTERColour CDM-TD 70W/830 RX7s 1CT/12	500 °C
928084705133	MASTERColour CDM-TD 70W/942 RX7s 1CT/12	500 °C

Order Code	Full Product Name	Bulb Temperature (Max)
928083605133	MASTERColour CDM-TD 150W/830 RX7s 1CT	650 °C
928084805133	MASTERColour CDM-TD 150W/942 RX7s 1CT	650 °C

## Light technical (1/3)

Order Code	Full Product Name	Chromaticity		Colour	
		Coordinate X (Nom)	Coordinate Y (Nom)	Code	Designation
928082205125	MASTERColour CDM-TD 70W/830 RX7s 1CT/12	0.434	0.398	830	Warm white (WW)
928084705133	MASTERColour CDM-TD 70W/942 RX7s 1CT/12	0.371	0.366	942	Cool White (CW)

Order Code	Full Product Name	Chromaticity		Colour	
		Coordinate X (Nom)	Coordinate Y (Nom)	Code	Designation
928083605133	MASTERColour CDM-TD 150W/830 RX7s 1CT	0.434	0.398	830	Warm white (WW)
928084805133	MASTERColour CDM-TD 150W/942 RX7s 1CT	0.371	0.366	942	Cool White (CW)

## Light technical (2/3)

Order Code	Full Product Name	Correlated Colour Temperature		Colour Rendering Index		Lumen Maintenance			Luminous Efficacy (rated) (Nom)	
		(Nom)	Index (Min)	(Nom)	10000 h (Nom)	2000 h (Min)	2000 h (Nom)	5000 h (Min)		5000 h (Nom)
928082205125	MASTERColour CDM-TD 70W/830 RX7s 1CT/12	3000 K	77	80	70 %	80 %	85 %	70 %	80 %	85 lm/W
928084705133	MASTERColour CDM-TD 70W/942 RX7s 1CT/12	4200 K	-	92	60 %	70 %	85 %	60 %	70 %	76 lm/W
928083605133	MASTERColour CDM-TD 150W/830 RX7s 1CT	3000 K	-	88	75 %	80 %	90 %	75 %	85 %	87 lm/W
928084805133	MASTERColour CDM-TD 150W/942 RX7s 1CT	4200 K	-	96	70 %	80 %	90 %	75 %	85 %	90 lm/W


## Light technical (3/3)

# MASTERColour CDM-TD


Order Code	Full Product Name	Luminous Flux (Nom)	Luminous Flux (Rated) (Nom)
928082205125	MASTERColour CDM-TD 70W/830 RX7s 1CT/12	6000 lm	6000 lm
928084705133	MASTERColour CDM-TD 70W/942 RX7s 1CT/12	5450 lm	5450 lm

Order Code	Full Product Name	Luminous Flux (Nom)	Luminous Flux (Rated) (Nom)
928083605133	MASTERColour CDM-TD 150W/830 RX7s 1CT	12750 lm	12750 lm
928084805133	MASTERColour CDM-TD 150W/942 RX7s 1CT	13650 lm	13650 lm

## Color Rendering Diagrams



LDCR\_CDM-TD\_70W-Colour rendering diagram



LDCR\_CDM-TD\_150W-Colour rendering diagram

