



Product description

MH-NaSc

Sodium Scandium Metal Halide Lamps consisting of a gasfilled glass bulb, which alternatively are clear or internal coated, and a quartz discharge tube (DT).

Benefits

- Energy saving solution with better color appearance and rendering property for conventional version.

Features

- Quartz discharge tube containing high-pressure mercury and a mixture of Sodium and Scandium halides, which contribute to multi-lines spectra; with Ar to aid ignition.
- Better colour rendering index around 60
- Luminous efficacy up to 90 lm/W
- Low wattage lamps with extra quartz tube around DT to prevent the risk of outer bulb shattering when abnormal operated or to the end of life.
- Universal operation position permitted

Application

- Stadium and sports facilities lighting
- Industrial and commercial lighting—factory
- supermarket and exhibition hall etc.
- Public lighting—square, station, port, airport etc.
- Decorative flood lighting—monument, buildings e.g.
- hotel

Controls and dimming

Dimmable	No
----------	----

Operating and electrical

Power (Rated) (Min)	- W
---------------------	-----

General information

Operating Position	H
System Description	na

Light technical

Colour Designation	Cool White (CW)
--------------------	-----------------

Approval and application

Order Code	Full Product Name	Energy Consumption kWh/1000 h	Mercury (Hg) Content (Nom)
928480200097	MH 175W/640 E40 CL U 1SL/12	192 kWh	28 mg
928480400097	MH 400W/640 E40 CL U 1SL/6	440 kWh	38 mg
928480310097	MH 250W/637 E40 CO U 1SL/12	275 kWh	33 mg

Order Code	Full Product Name	Energy Consumption kWh/1000 h	Mercury (Hg) Content (Nom)
928480410097	MH Quartz 400W/637 E40 CO U 1SL/6	440 kWh	38 mg
928484600092	MH 150W/640 E27 CL 1SL/24	165 kWh	11 mg

Operating and electrical

Order Code	Full Product Name	Lamp Current (EM) (Nom)	Voltage (Max)	Voltage (Min)	Voltage (Nom)	Power (Rated) (Max)	Power (Nom)
928480200097	MH 175W/640 E40 CL U 1SL/12	1.5 A	147 V	117 V	132 V	- W	175.0 W
928480400097	MH 400W/640 E40 CL U 1SL/6	3.25 A	150 V	120 V	135 V	440.0 W	400.0 W
928480310097	MH 250W/637 E40 CO U 1SL/12	2.1 A	148 V	118 V	133 V	- W	250 W
928480410097	MH Quartz 400W/637 E40 CO U 1SL/6	3.25 A	150 V	120 V	135 V	440.0 W	400.0 W
928484600092	MH 150W/640 E27 CL 1SL/24	1.8 A	105 V	85 V	95 V	- W	153 W

General information

Order Code	Full Product Name	Cap-Base	Life To		
			20% Failures (Nom)	Life To 50% Failures (Nom)	Life To 5% Failures (Nom)
928480200097	MH 175W/640 E40 CL U 1SL/12	E40	-	10000 h	-
928480400097	MH 400W/640 E40 CL U 1SL/6	E40	-	20000 h	-
928480310097	MH 250W/637 E40 CO U 1SL/12	E40	-	10000 h	-

Order Code	Full Product Name	Cap-Base	Life To		
			20% Failures (Nom)	Life To 50% Failures (Nom)	Life To 5% Failures (Nom)
928480410097	MH Quartz 400W/637 E40 CO U 1SL/6	E40	-	16000 h	-
928484600092	MH 150W/640 E27 CL 1SL/24	E27	5000 h	10000 h	2000 h

Luminaire design requirements

Order Code	Full Product Name	Bulb Temperature (Max)
928480200097	MH 175W/640 E40 CL U 1SL/12	400 °C
928480400097	MH 400W/640 E40 CL U 1SL/6	400 °C
928480310097	MH 250W/637 E40 CO U 1SL/12	400 °C

Order Code	Full Product Name	Bulb Temperature (Max)
928480410097	MH Quartz 400W/637 E40 CO U 1SL/6	400 °C
928484600092	MH 150W/640 E27 CL 1SL/24	450 °C

Light technical (1/2)

Order Code	Full Product Name	Chromaticity	Chromaticity	Colour		Lumen	Lumen	
		Coordinate X (Nom)	Coordinate Y (Nom)	Code	Correlated Colour Temperature (Nom)	Rendering Index (Nom)	Maintenance 1000 h (Nom)	Maintenance 2000 h (Nom)
928480200097	MH 175W/640 E40 CL U 1SL/12	375	390	640	4300 K	60	-	80 %
928480400097	MH 400W/640 E40 CL U 1SL/6	390	400	640	3900 K	60	-	85 %
928480310097	MH 250W/637 E40 CO U 1SL/12	405	395	637	3600 K	61	85 %	-
928480410097	MH Quartz 400W/637 E40 CO U 1SL/6	405	395	637	-	61	85 %	-
928484600092	MH 150W/640 E27 CL 1SL/24	385	390	640	4000 K	65	-	75 %

Light technical (2/2)

Order Code	Full Product Name	Lumen	Luminous	Luminous	Luminous
		Maintenance 5000 h (Nom)	Efficacy (rated) (Nom)	Flux (Rated) (Min)	Flux (Rated) (Nom)
928480200097	MH 175W/640 E40 CL U 1SL/12	-	80 lm/W	11050 lm	14000 lm
928480400097	MH 400W/640 E40 CL U 1SL/6	-	97.5 lm/W	34000 lm	39000 lm
928480310097	MH 250W/637	-	76 lm/W	17200 lm	19000 lm

Order Code	Full Product Name	Lumen	Luminous	Luminous	Luminous
		Maintenance 5000 h (Nom)	Efficacy (rated) (Nom)	Flux (Rated) (Min)	Flux (Rated) (Nom)
928480410097	MH Quartz 400W/637 E40 CO U 1SL/6	-	83.5 lm/W	25900 lm	33400 lm
928484600092	MH 150W/640 E27 CL 1SL/24	60 %	95 lm/W	13050 lm	14500 lm

Mechanical and housing

Order Code	Full Product Name	Bulb Finish	Bulb Shape
928480200097	MH 175W/640 E40 CL U 1SL/12	Clear	ED90
928480400097	MH 400W/640 E40 CL U 1SL/6	Clear	ED120
928480310097	MH 250W/637 E40 CO U 1SL/12	Coated glass	ED90

Order Code	Full Product Name	Bulb Finish	Bulb Shape
928480410097	MH Quartz 400W/637 E40 CO U 1SL/6	Coated glass	ED120
928484600092	MH 150W/640 E27 CL 1SL/24	Clear	ED55

