



Product Description

MSR

MSR – bright vivid colours, always The high colour rendering index of the single ended MSR series ensures that everyone in the audience can enjoy the true colours of the scenery, the stage props, the players and their costumes – in fact everything that is on stage can be made bright and vivid in daylight quality light. Also, thanks to the single ended lamp concept, the luminaire has optimal light collection and direction possibilities to help ensure brightness on stage exactly where and when it is needed. In addition, the MSR can be used in any burning position for easy set-up and convenience.

Benefits

- High luminous efficacy
- Compact arc (6 - 10 mm)
- Good colour rendering
- Dimmable with a stable colour temperature

Features

- Run-up time 2 minutes
- Restrike time 5 - 10 minutes, depending on cooling conditions

Application

- Studios and discos


Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Versions



Dimensional drawing



Product	D (max)	O	L (min)	L (max)	L	C (max)	F
MSR 700/2 1CT/8	30 mm	8.0 mm	74 mm	76 mm	75 mm	152 mm	42 mm

Controls and Dimming	
Dimmable	No
General Information	
Life To 50% Failures (Nom)	1000 h
Main Application	Studio/Disco
Operating Position	UNIVERSAL
System Description	Cold Strike
Light Technical	
Colour Code	2

Operating and Electrical

Order Code	Full Product Name	Lamp Current (Nom)	Power (Rated) (Nom)
928171505114	MSR 700/2 1CT/8	11 A	700 W

Order Code	Full Product Name	Lamp Current (Nom)	Power (Rated) (Nom)
928171605115	MSR 575/2 10H 1CT/4	6.75 A	575 W

General Information

Order Code	Full Product Name	Cap-Base
928171505114	MSR 700/2 1CT/8	G22

Order Code	Full Product Name	Cap-Base
928171605115	MSR 575/2 10H 1CT/4	GX9.5

Light Technical

Order Code	Full Product Name	Correlated			
		Colour Temperature (Nom)	Colour Rendering Index (Nom)	Luminous Flux (Min)	Luminous Flux (Nom)
928171505114	MSR 700/2 1CT/8	7200 K	80	48000 lm	55000 lm

Order Code	Full Product Name	Correlated			
		Colour Temperature (Nom)	Colour Rendering Index (Nom)	Luminous Flux (Min)	Luminous Flux (Nom)
928171605115	MSR 575/2 10H 1CT/4	6990 K	70	42750 lm	47500 lm

