



Reliable Compact Fluorescent lamp non- integrated

PL-L Essential

Energy-saving compact fluorescent non-integrated lamp

Benefits

- Good color rendering (CRI >80)
- Long life and sustainable light output

Features

- 4-pin base without starter and capacitor
- Fluorescent tri-phosphor technology

Application

- Designed for use in general lighting in shops and residential areas

PL-L Essential

Approval and application

Mercury (Hg) Content (Nom)	3.0 mg
----------------------------	--------

Controls and dimming

Dimmable	Yes
----------	-----

General information

Cap-Base	2G11
Life To 50% Failures Preheat (Nom)	12000 h

Light technical

Colour Code	865
Colour Designation	Cool Daylight
Correlated Colour Temperature (Nom)	6500 K
Colour Rendering Index (Nom)	80
Lumen Maintenance 2000 h (Nom)	85 %
Lumen Maintenance 5000 h (Nom)	80 %
Luminous Efficacy (rated) (Nom)	69 lm/W

Operating and electrical

Order Code	Full Product Name	Lamp Current (Nom)	Voltage (Nom)	Power (Nom)
927933686503	PL-L Essential 36W/865/4P 1CT/50	0.435 A	106 V	36 W
927933786503	PL-L Essential 55W/865/4P 1CT/50	0.550 A	101 V	55 W

Light technical

Order Code	Full Product Name	Luminous Flux (Nom)
927933686503	PL-L Essential 36W/865/4P 1CT/50	2550 lm

Order Code	Full Product Name	Luminous Flux (Nom)
927933786503	PL-L Essential 55W/865/4P 1CT/50	3900 lm

