



Reliable Compact Fluorescent lamp non- integrated

PL-L Essential

Energy-saving compact fluorescent non-integrated lamp

Benefits

- Good color rendering (CRI >80)
- Long life and sustainable light output

Features

- 4-pin base without starter and capacitor
- Fluorescent tri-phosphor technology

Application

- Designed for use in general lighting in shops and residential areas

PL-L Essential

Versions



Essential 36 W 2G11 4P

Approval and Application

Mercury (Hg) Content (Nom) 3.0 mg

Controls and Dimming

Dimmable Yes

General Information

Cap-Base 2G11

Life To 50% Failures Preheat (Nom) 12000 h

Light Technical

Colour Code 865

Colour Designation Cool Daylight

Correlated Colour Temperature (Nom) 6500 K

Colour Rendering Index (Nom) 80

Lumen Maintenance 2000 h (Nom) 85 %

Lumen Maintenance 5000 h (Nom) 80 %

Luminous Efficacy (rated) (Nom) 69 lm/W

Operating and Electrical

Order Code	Full Product Name	Lamp Current (Nom)	Voltage (Nom)	Power (Rated) (Nom)
927933686503	PL-L Essential 36W/865/4P 1CT/50	0.435 A	106 V	36 W
927933786503	PL-L Essential 55W/865/4P 1CT/50	0.550 A	101 V	55 W

Light Technical

Order Code	Full Product Name	Luminous Flux (Nom)	Order Code	Full Product Name	Luminous Flux (Nom)
927933686503	PL-L Essential 36W/865/4P 1CT/50	2550 lm	927933786503	PL-L Essential 55W/865/4P 1CT/50	3900 lm

