



SmartBright G2 LED Floodlight

BVP151 LED150/WW 220-240V 150W AWB CE

14300 lm - 150 W - 3000 K

SmartBright G2 LED Floodlight delivers high lumen efficacy, with long lifetime and reliable design. Asymmetric optical distribution improves light effect. The product is an ideal solution for most floodlight applications.

Product data

General Information	
Lamp colour code	730 warm white
Light source replaceable	No
Driver included	Yes
Optical cover/lens type	FG [Flat glass]
Control interface	-
Connection	Flying leads/wires
Cable	Cord 0.6 m without plug
Protection class IEC	Safety class I (I)
Flammability mark	NO [-]
CE mark	CE mark
Optic type outdoor	Asymmetrical
Light source engine type	LED
Serviceability class	Class C, luminaire without serviceable parts, not serviceable

Light Technical	
Standard tilt angle post-top	-

Standard tilt angle side entry	-
--------------------------------	---

Operating and Electrical	
Input Voltage	220-240 V
Input frequency	50 or 60 Hz
Power factor (min.)	0.9

Controls and Dimming	
Dimmable	No

Mechanical and Housing	
Housing material	Aluminum die-cast
Optical cover/lens material	Tempered glass
Mounting device	MBA [Mounting bracket adjustable]
Optical cover/lens shape	Flat
Optical cover/lens finish	Clear
Overall length	430 mm
Overall width	335 mm
Overall height	60 mm


SmartBright G2 LED Floodlight

Colour	Dark Grey
Approval and Application	
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Surge protection (common/differential)	Luminaire surge protection level up to 4 kV differential mode and 4 kV common mode
Initial Performance (IEC Compliant)	
Initial luminous flux (system flux)	14300 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	95 lm/W
Lamp colour temperature	3000 K
Colour Rendering Index	80
Initial input power	150 W
Power consumption tolerance	+/-10%

Application Conditions	
Ambient temperature range	-25 to +40 °C
Product Data	
Full product code	871016334359499
Order product name	BVP151 LED150/WW 220-240V 150W AWB CE
EAN/UPC – product	8710163343594
Order code	911401816280
SAP numerator – quantity per pack	1
Numerator – packs per outer box	2
SAP material	911401816280
SAP net weight (piece)	4.960 kg



Dimensional drawing



BVP151 LED Underwater

