



# Plusline Small

## Plusline S 300W R7s 230V 1CT/10X10F

Mains-voltage linear lamp giving white halogen light

### Product data

General Information	
Cap base	R7S [ R7s]
Burning Position	UNIVERSAL [ Any/Universal]
Nominal lifetime (nom.)	2000 h
Rated Lifetime	2000 h
Light Technical	
Lamp Luminous Flux 25°C EL (Nom)	5114 lm
Colour Temperature, horizontal (Nom)	2900 K
Lamp Luminous Efficacy EM (Nom)	17 lm/W
Colour Rendering Index,horiz (Nom)	100
Operating and Electrical	
Power (Rated) (Nom)	300 W
Lamp current (nom.)	1.3 A
Starting time (nom.)	0.0 s
Voltage (Nom)	230 V
Controls and Dimming	
Dimmable	Yes

Mechanical and Housing	
Lamp Finish	Clear
Bulb shape	T3 [ T 12mm (T3)]
Luminaire Design Requirements	
Bulb temperature (max.)	900 °C
Pinch temperature (max.)	350 °C
Product Data	
Full product code	872790080895700
Order product name	Plusline S 300W R7s 230V 1CT/10X10F
EAN/UPC – product	8727900808957
Order code	924735444201
SAP numerator – quantity per pack	1
Numerator – packs per outer box	100
SAP material	924735444201
SAP net weight (piece)	0.010 kg
ILCOS code	HDG//RS-300-230-R7s-114,2

## Plusline Small

### Dimensional drawing



Product	D (max)	B (max)	B	B (min)	C (max)
Plusline S 300W R7s 230V 1CT/10X10F	12 mm	115.8 mm	114.2 mm	112.6 mm	117.6 mm

Plusline S 300W R7s 230V 1CT/10X10F

