



Plusline Small

Plusline S 200W R7s 230V 1CT/10X10F

Mains-voltage linear lamp giving white halogen light

Product data

General Information	
Cap base	R7S [R7s]
Burning Position	UNIVERSAL [Any/Universal]
Nominal lifetime (nom.)	2000 h
Rated Lifetime	2000 h
Light Technical	
Lamp Luminous Flux 25°C EL (Nom)	3000 lm
Colour Temperature, horizontal (Nom)	2900 K
Lamp Luminous Efficacy EM (Nom)	15 lm/W
Colour Rendering Index,horiz (Nom)	100
Operating and Electrical	
Power (Rated) (Nom)	200 W
Lamp current (nom.)	0.87 A
Starting time (nom.)	0.0 s
Voltage (Nom)	230 V
Controls and Dimming	
Dimmable	Yes

Mechanical and Housing	
Lamp Finish	Clear
Bulb shape	T3 [T 12mm (T3)]
Luminaire Design Requirements	
Bulb temperature (max.)	900 °C
Pinch temperature (max.)	350 °C
Product Data	
Full product code	872790080909100
Order product name	Plusline S 200W R7s 230V 1CT/10X10F
EAN/UPC – product	8727900809091
Order code	924735744201
SAP numerator – quantity per pack	1
Numerator – packs per outer box	100
SAP material	924735744201
SAP net weight (piece)	0.010 kg
ILCOS code	HDG//RS-200-230-R7s-114,2

Plusline Small

Dimensional drawing



Product	D (max)	B (max)	B	B (min)	C (max)
Plusline S 200W R7s 230V 1CT/10X10F	12 mm	115.8 mm	114.2 mm	112.6 mm	117.6 mm

Plusline S 200W R7s 230V 1CT/10X10F

