



UniFlood M G2

BVP353 72LED RGBNW 220V L57 10 DMX

Philips UniFlood M gen2 is a cost-effective, exterior-rated architectural LED floodlight that's designed for façade, landscape and outdoor flood lighting applications. The robust, modular, rectangular design features highly-efficient optics, making it ideal for illuminating everything from multi-storey façades and bridges to landmarks and monuments. This LED floodlight is available in white, monochromatic colors, RGB, RGBW and tunable white. It comes with six different spread lenses ranging from narrow spot to wide flood and has DMX512/RDM control option. A truly modular floodlight that gives architects and designers the freedom to explore a wide range of concepts and designs with no limitations.

Warnings and Safety

- For outdoor use only.

Product data

General Information		Operating and Electrical	
Driver included	Yes	Input Voltage	220 to 240 V
Lighting Technology	LED	Line Frequency	50 to 60 Hz
Light Technical		Input Frequency	50 to 60 Hz
Luminous Flux	7,515 lumen	Inrush current	60 A
Correlated Color Temperature (Nom)	-	Power Factor (Fraction)	0.95
Luminous Efficacy (rated) (Nom)	50 lm/W	Connection	Flying leads/wires and 2 Push-in connector 4-pole
Color rendering index (CRI)	>80	Cable	Cable 0.5 m without plug 3-pole and 2 Cables 0.5 m with connector 4-pole
Light source color	RGBW		
Optical cover/lens type	Clear glass		

UniFlood M G2

Temperature

Ambient temperature range -40 to +50 °C

Controls and Dimming

Dimmable Yes

Control interface Dynamic DMX/RDM

Mechanical and Housing

Housing Material Aluminum extruded

Optical cover/lens material Acrylate

Housing Color Dark gray

Overall length 569 mm

Overall width 140 mm

Overall height 149 mm

Effective projected area 0.078 m²

Dimensions (Height x Width x Depth) 149 x 140 x 569 mm

Approval and Application

Ingress protection code IP66 [Dust penetration-protected, jet-proof]

Mech. impact protection code IK06 [1 J]

Protection class IEC Safety class I

Flammability mark For mounting on normally flammable surfaces

CE mark CE mark

Initial Performance (IEC Compliant)

Luminous flux tolerance +/-10%

Power consumption tolerance +/-10%

Product Data

Full product code 871951492759999

Order product name BVP353 72LED RGBNW 220V L57 10 DMX

Order code 911401748383

Numerator - Quantity Per Pack 1

Numerator - Packs per outer box 2

Material number (12NC) 911401748383

Full product name BVP353 72LED RGBNW 220V L57 10 DMX

EAN/UPC - Case 8719514927599



Dimensional drawing

