



ZXP399 DMX Controls and Accessories

ZXP399 sub-controller 12V 8 port DMX

12 DC V Hz - Finger-protected - CE mark - Black -

The ZXP399 DMX Controls and Wiring Accessories are to be used with our architectural and facade lighting luminaires (UniFlood C, M and G, UniStrip G4, UniEdge, UniDot G2, UniString and UniBar).;DMX Controls include a main controller, stand-alone controller, sub-controllers, DMX amplifier and DMX addressing device.;Main Controller: Industrial computer that can control up to 6,000 DMX universes.;Stand-alone Controller: Fits all medium applications with up to 700 DMX universes.;Wiring accessories include leader and jump cables with male and female IP67 connectors and end-caps.;Addressing Device: Hand-held device that can write DMX addresses to a whole run on-site within minutes.;DMX Amplifier: Compact, IP65 and low-power repeater that can amplify the DMX signal for up 100 metres.

Product data

General Information		Approval and Application	
CE mark	CE mark	Ingress protection code	IP20 [Finger-protected]
Colour	Black	Product Data	
Operating and Electrical		Full product code	871951494690399
Input Voltage	12 DC V	Order product name	ZXP399 sub-controller 12V 8 port DMX
Input frequency	- Hz		
Mechanical and Housing			
Overall length	277.6 mm		
Overall width	193 mm		
Overall height	66 mm		
Dimensions (height x width x depth)	66 x 193 x 278 mm (2.6 x 7.6 x 10.9 in)		


ZXP399 DMX Controls and Accessories

EAN/UPC – product	8719514946903
Order code	911401756662
SAP numerator – quantity per pack	1
Numerator – packs per outer box	2
SAP material	911401756662

SAP net weight (piece)	1.499 kg
------------------------	----------



Dimensional drawing



ZXP399 sub-controller 12V 8 port DMX

