



RCS750 3-circuit square track system – flexible and multifunctional

3-circuit Square RCS750

The RCS750 3-circuit square track system is made up of a solid aluminium track available in lengths of 1, 2, 3 and 4 m with four electrical conductors. Any given configuration can be created easily: horizontal or vertical, mounted on or in the ceiling, on the wall or on free-standing panels. The system can also be used as a floating structure. All luminaires have a separate power supply and can be switched selectively. They can be moved easily to change the lighting and presentation. In this way, a multifunctional track system can be created for accent lighting as well as for suspending advertising and decorative material. A range of adaptors, power supply connections and mounting accessories is also available.

Benefits

- Flexible 3-circuit track system for the professional user, allowing any required configuration to be created relatively easily
- All luminaires have separate power switching so they can easily be moved, for example to create changing atmospheres in shop windows or interiors
- Can be applied as a 'floating' structure using the suspension tubes and clamps provided

Features

- -

Application

- Retail
- Indoor architectural lighting

3-circuit Square RCS750

Specifications

Type	RCS750
Circuit	3-circuit power track (3C)
Length version	1000 in mm (L1000)
	2000 in mm (L2000)
	3000 in mm (L3000)
	4000 in mm (L4000)
Color	White (WH)
	Black (BK)
	Aluminum (ALU)

Installation	Three circuits 250 V AC, 16 A, 3 x 3,7 KvA (total power supply) Also possible to connect a 3-phase supply (230 - 400 V 16 A) when there will be a threefold increase in power rating i.e. 11.1 kW Integrated fastening holes (distance 1000 mm, load 5 x 5 kg max, torque 2.5 Nm)
Accessory	Range of adapters, power supply connections and mounting accessories
Main applications	Retail

Versions

