



Lighting your way to success

SportsStar-BVP621/BVP622/EVP622

Philips SportsStar LED Floodlight sets the standard in high quality optical distribution with high performance and low light pollution (or effective light control). From Sports to Area Lighting, our system, including the high masts needed, projects the light exactly where it should be going. Choose the right illumination levels for any given setting with Philips SportsStar LED Floodlight.

Benefits

- Fit for both high mast area and sports application
- Multiple lens covers as much as of customer needs
- Compatible with systems, including Philips Arenavision system
- Robust quality and reliability
- Comply with HDTV broadcasting requirement

Features

- Both integrated version and remote version
- Wide range of optics
- DALI, 1-10V and DMX control interface
- Salty Spray 1,000hrs
- Typical lifetime up to 50K hours (L70B50)
- Flicker free (<1%) performance

SportsStar-BVP621/BVP622/EVP622

Application

- Airport Apron
- Port & Container Yard
- Large industrial areas
- Large Car Park Areas
- Building facades
- Transportation Terminals & Tollways
- Golf Driving Range
- General flood lighting
- Professional Sports Stadium
- Recreational Sports Stadium

Versions



EVP622 GM

Accessories



Ordercode 911401597251

SportsStar-BVP621/BVP622/EVP622

Approval and Application

Mech. impact protection code	IK08
Surge Protection (Common/Differential)	Luminaire surge protection level up to 15 kV differential mode and 15 kV common mode

Controls and Dimming

Dimmable	No
----------	----

General Information

CE mark	CE mark
Light source colour	-
Optical cover/lens type	No
Driver included	Yes

Initial Performance (IEC Compliant)

Init. Corr. Colour Temperature	- K
Init. Colour Rendering Index	-

Application Conditions

Order Code	Full Product Name	Maximum dim level
911401649204	EVP622 IP66 960W 220-240V GM 5C O	-
911401849098	EVP622 IP66 960W 220-240V GM	Not applicable

General Information (1/2)

Order Code	Full Product Name	Luminaire		Lamp	
		light beam spread	Flammability mark	family code	Light source replaceable
911401649204	EVP622 IP66 960W	-	-	-	No

Order Code	Full Product Name	Luminaire		Lamp	
		light beam spread	Flammability mark	family code	Light source replaceable
	220-240V GM 5C O				
911401849098	EVP622 IP66 960W 220-240V GM	-	NO	-	-

General Information (2/2)

Order Code	Full Product Name	Number of gear units	Optic type
911401649204	EVP622 IP66 960W 220-240V GM 5C O	1 unit	-

Order Code	Full Product Name	Number of gear units	Optic type
911401849098	EVP622 IP66 960W 220-240V GM	2 units	-

Mechanical and Housing

Order Code	Full Product Name	Colour
911401649204	EVP622 IP66 960W 220-240V GM 5C O	Black

Order Code	Full Product Name	Colour
911401849098	EVP622 IP66 960W 220-240V GM	black

Light Technical

Order Code	Full Product Name	Standard tilt angle side entry	Standard tilt angle posttop
911401649204	EVP622 IP66 960W 220-240V GM 5C O	-	-

Order Code	Full Product Name	Standard tilt angle side entry	Standard tilt angle posttop
911401849098	EVP622 IP66 960W 220-240V GM	-	-

