



# UniEdge – Make Your Boundaries Stand Out

## UniEdge

UniEdge is a surface-mounted, exterior-rated and compact-sized architectural LED edge lighting luminaire that is designed for façade and outdoor decorative lighting applications. The robust mechanical and unique optical designs make UniEdge ideal for edges lighting on windows and doors inner frames, building façades, landmarks and monuments. Available in white, monochromatic colours, RGB, RGBW and tunable white. Unique spread lens with a DMX control option available to give architects and designers the freedom to explore a wide range of concepts and design with no limitations.

### Benefits

- Unique Optical Distribution 3x90° to highlight the inner frames or outer edges of windows, balconies or doors.
- Compact Size, Lightweight and Tilttable Brackets.
- Through wiring for power and DMX512 Signal.

### Features

- Robust design and IP66 for outdoor use
- Unique 3x90° optical distribution to illuminate architectural edges
- Drainage design to reduce dirt and water accumulation
- Adjustable -5° to +85° tilting angle
- Through wiring for power and DMX data via IP67 connectors

### Application

- Bridges, Monuments, Facades
- Landscaping
- Parks and plazas

### Warnings and Safety


- For outdoor use only

# UniEdge

## Versions



## Product details



UniEdge Photo



UniEdge Photo



UniEdge Photo

## Application Conditions

Maximum dim level	13%
-------------------	-----

## Approval and Application

Mech. impact protection code	IK06
------------------------------	------

## Controls and Dimming

Dimmable	Yes
----------	-----

## General Information

Luminaire light beam spread	3° x 90°
-----------------------------	----------

CE mark	CE mark
---------	---------

Optical cover/lens type	CLFT
-------------------------	------

Driver included	No
-----------------	----

Flammability mark	F
-------------------	---

Light source replaceable	No
--------------------------	----

## Initial Performance (IEC Compliant)

Init. Colour Rendering Index	80
------------------------------	----

## Light Technical

Standard tilt angle posttop	-
-----------------------------	---

## Mechanical and Housing

Colour	Dark Grey
--------	-----------

## General Information

Order Code	Full Product Name	Light source colour
911401739782	BCP390 4LED 30K 24V 3x90 DMX	Warm white
911401739802	BCP390 4LED 40K 24V 3x90 DMX	Neutral white

## Initial Performance (IEC Compliant)

Order Code	Full Product Name	Init. Corr. Colour Temperature	Initial luminous flux
911401739782	BCP390 4LED 30K 24V 3x90 DMX	3000 K	124 lm
911401739802	BCP390 4LED 40K 24V 3x90 DMX	4000 K	142 lm

