

# UniStrip G4 – Best-in-Class Linear LED Surface Mounted Luminaire for Exterior Fixed and Dynamic Architectural Lighting Applications

## UniStrip G4

UniStrip G4 is a surface-mounted, exterior-rated LED luminaire that is designed for façade and outdoor architectural lighting applications. One family that fits all your needs, wall washing, grazing and also linear flood lighting. The robust mechanical and unique optical designs make it ideal for illuminating buildings facades, bridges, overpasses and any application that requires a linear lighting solution. Available in white, monochromatic colours, RGB, RGBW and tunable white and DMX control option available with up to 8 pixels (8IDs) to give architects and designers the freedom to explore a wide range of concepts and design with no limitations.

### Benefits

- High and Low Power LED versions available
- Various spread lenses that fit all applications
- Adjustable brackets and through wiring for end-to-end connection

# UniStrip G4

## Features

- Six sub-families with power ranges from 3 W to 120 W
- DC and AC powered versions
- Narrow, medium, wide and asymmetric beams available
- Optional glare shields for more visual comfort


## Application

- Bridges, Monuments, Facades
- Landscaping
- Parks and plazas

## Warnings and Safety

- For outdoor use only

## Versions



Application Conditions	
Maximum dim level	10%
Approval and Application	
Mech. impact protection code	IK06
Controls and Dimming	
Dimmable	Yes
General Information	
CE mark	CE mark
Driver included	Yes
Flammability mark	F
Light source replaceable	No
Number of gear units	1 unit
Optic type	Asymmetrical
Light Technical	
Standard tilt angle side entry	-
Standard tilt angle posttop	-
Mechanical and Housing	
Colour	Dark Grey

## General Information

Order Code	Full Product Name	Luminaire light beam		Optical cover/ lens type
		spread	Light source colour	
911401750912	BCP383 24LED 30K 220V A2 L100 DMX	16° x 35°	Warm white	GT
911401750982	BCP383 24LED RGBNW 220V A4 L100 DMX	25° x 40°	Red, green, blue and white	CLFT

## UniStrip G4

### Initial Performance (IEC Compliant)

Order Code	Full Product Name	Init. Corr. Colour	Init. Colour	
		Temperature	Rendering Index	Initial luminous flux
911401750912	BCP383 24LED 30K 220V A2 L100 DMX	3000 K	80	2459 lm
911401750982	BCP383 24LED RGBNW 220V A4 L100 DMX	- K	-	1639 lm

