



SmartBright Slim panel KR

RC091V LED45S/857 PSU W32L128 KR

Polystyrene bowl/cover prismatic - 120° x 120°

The new Smartbright slim panel offers customers excellent solutions for their lighting needs. It is durable, energy-efficient and comes with a 3-year warranty.

Product data

General Information		Controls and Dimming	
Lamp colour code	857 daylight	Dimmable	No
Driver included	Yes		
Optical cover/lens type	Polystyrene bowl/cover prismatic	Mechanical and Housing	
Luminaire light beam spread	120° x 120°	Housing material	Aluminum extruded
Control interface	-	Optical cover/lens material	Acrylate
Cable	Cable 0.75 m without plug	Optical cover/lens finish	Matte
Protection class IEC	Safety class I (I)	Overall length	1285 mm
CE mark	-	Overall width	320 mm
Warranty period	3 years	Overall height	27.6 mm
Constant light output	No	Colour	White
Number of products on MCB (16 A type B)	30	Approval and Application	
LED engine type	LED	Ingress protection code	IP20 [Finger-protected]
		Mech. impact protection code	IK02 [0.2 J standard]
Operating and Electrical		Initial Performance (IEC Compliant)	
Input Voltage	220 to 240 V	Initial luminous flux (system flux)	4500 lm
Input frequency	50 or 60 Hz	Luminous flux tolerance	+/-10%
Power factor (min.)	0.9	Initial LED luminaire efficacy	90 lm/W

SmartBright Slim panel KR

Lamp colour temperature	5700 K
Colour Rendering Index	>80
Initial chromaticity	857 daylight
Initial input power	50 W
Power consumption tolerance	+/-10%

Application Conditions

Ambient temperature range	-10 to +40 °C
---------------------------	---------------


Product Data

Full product code	871016334135499
-------------------	-----------------

Order product name	RC091V LED45S/857 PSU W32L128 KR
EAN/UPC – product	8710163341354
Order code	911401746902
SAP numerator – quantity per pack	1
SAP numerator – packs per outer box	4
Material no. (12 NC)	911401746902
SAP net weight (piece)	2.960 kg



Dimensional drawing



RC091V LED26S/LED36S PSU

