



# MASTER PL-S 2 Pin

## MASTER PL-S 13W/865/2P 1CT/10

MASTER PL-S is an efficient low-wattage compact fluorescent lamp, typically used for decorative and orientation purposes. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. The 2-pin version is designed for operation on electromagnetic gear and is provided with a plug-in/pull-out lamp base

### Warnings and Safety

- Use only with electromagnetic control gear
- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position
- Dimming is not possible
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

### Product data

General Information		Colour Rendering Index,horiz (Nom)	
Cap base	GX23 [ GX23]		82
Life to 50% failures (nom.)	8000 h		
Light Technical		Operating and Electrical	
Colour Code	865 [ CCT of 6,500 K]	Power (Rated) (Nom)	13.0 W
Lamp Luminous Flux 25°C EL (Nom)	820 lm	Lamp current (nom.)	0.290 A
Colour Designation	Cool Daylight	Voltage (Nom)	56 V
Lumen maintenance 2,000 hours (nom.)	82 %	Controls and Dimming	
Lumen maintenance 5,000 hours (nom.)	77 %	Dimmable	No
Colour Temperature, horizontal (Nom)	6500 K		
Lamp Luminous Efficacy EM (Nom)	63 lm/W		

# MASTER PL-S 2 Pin

Mechanical and Housing	
Cap-base information	2P

  

Approval and Application	
Energy efficiency label (EEL)	B
Mercury (Hg) content (nom.)	1.4 mg

  

Product Data	
Full product code	871869965545700

Order product name	MASTER PL-S 13W/865/2P 1CT/10
EAN/UPC – product	8718699655457
Order code	927902886566
SAP numerator – quantity per pack	1
Numerator – packs per outer box	10
SAP material	927902886566
SAP net weight (piece)	35.000 g

## Dimensional drawing

□ □

Product	D (max)	D1 (max)	C (max)
MASTER PL-S 13W/865/2P 1CT/10	27.1 mm	13 mm	178.2 mm

PL-S 13W/865/2P

