



TL-D LIFEMAX Super 80 JIS

TL-D 18W/865 JIS 1SL/25

The TL-D LIFEMAX Super 80 lamp offers more lumens per watt and better color rendering than TL-D standard colors. Furthermore, it has a lower mercury content. The lamp can be operated in existing TL-D luminaires. The lamp is complying with Japanese Industrial Standard.

Product data

General Information		Controls and Dimming	
Cap base	G13 [Medium Bi-Pin Fluorescent]	Dimmable	No
Life to 10% failures (nom.)	10000 h		
Life to 50% failures (nom.)	13000 h		
Life to 50% failures preheat (nom.)	20000 h		
Light Technical		Mechanical and Housing	
Colour Code	865 [CCT of 6,500 K]	Cap-base information	Green [Green Cap]
Lamp Luminous Flux 25°C EL (Nom)	1350 lm		
Colour Designation	Cool Daylight		
Lumen maintenance 2,000 hours (nom.)	96 %		
Lumen maintenance 5,000 hours (nom.)	94 %		
Colour Temperature, horizontal (Nom)	6500 K		
Lamp Luminous Efficacy EM (Nom)	75 lm/W		
Colour Rendering Index,horiz (Nom)	80		
Operating and Electrical		Approval and Application	
Power (Rated) (Nom)	19 W	Mercury (Hg) content (nom.)	2.0 mg
Lamp current (nom.)	0.35 A		
Voltage (Nom)	65 V		
Product Data			
Full product code	871150062995101		
Order product name	TL-D 18W/865 JIS 1SL/25		
EAN/UPC – product	8711500629951		
Order code	927919986532		
SAP numerator – quantity per pack	1		
Numerator – packs per outer box	25		
Material no. (12 NC)	927919986532		
SAP net weight (piece)	0.080 kg		

TL-D LIFEMAX Super 80 JIS

Dimensional drawing

Product	D (max)	A (max)	B (max)	B (min)	C (max)
TL-D 18W/865 JIS 1SL/25	28 mm	581.3 mm	588.4 mm	585.8 mm	595.5 mm

TL-D 18W/865 JIS

