



MASTER TL5 High Output

MASTER TL5 HO 24W/865 SLV/40

Low-pressure mercury discharge lamps with a tubular 16 mm envelope

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information		Operating and Electrical	
Cap base	G5 [G5]	Lamp Luminous Efficacy EM (Nom)	72 lm/W
Life to 50% failures preheat (nom.)	30000 h	Colour Rendering Index,horiz (Max)	85
Features	na [Not Applicable]	Colour Rendering Index,horiz (Min)	80
System description	High Output (HO)	Colour Rendering Index,horiz (Nom)	82
LSF preheat 2,000 hours rated	99 %	LLMF 2000 h Rated	96 %
LSF preheat 4,000 hours rated	99 %	LLMF 4000 h Rated	95 %
LSF preheat 6,000 hours rated	99 %	LLMF 6000 h Rated	94 %
LSF preheat 8,000 hours rated	99 %	LLMF 8000 h Rated	93 %
LSF preheat 16,000 hours rated	97 %	LLMF 12000 h Rated	92 %
LSF preheat 20,000 hours rated	84 %	LLMF 16000 h Rated	91 %
		LLMF 20000 h Rated	90 %
Light Technical		Temperature	
Colour Code	865 [CCT of 6,500 K]	Design temperature (nom.)	35 °C
Lamp Luminous Flux 25°C EL (Nom)	1825 lm		
Lamp Luminous Flux (Nom)	1575 lm		
Colour Designation	Cool Daylight		
Luminous Efficacy (@ Max Lumen, Rated) (Nom)	81 lm/W		
Colour Temperature, horizontal (Nom)	6500 K		

MASTER TL5 High Output

Controls and Dimming

Dimmable	Yes
----------	-----

Mechanical and Housing

Cap-base information	Green Plate
----------------------	-------------

Approval and Application


Energy efficiency label (EEL)	A
Mercury (Hg) content (nom.)	1.4 mg
Energy consumption kWh/1,000 hours	25 kWh

Product Data

Full product code	871150064393355
-------------------	-----------------

Order product name	MASTER TL5 HO 24W/865 SLV/40
EAN/UPC – product	8711500643933
Order code	927928086555
SAP numerator – quantity per pack	1
Numerator – packs per outer box	40
Material no. (12 NC)	927928086555
SAP net weight (piece)	52.000 g
ILCOS code	FDH-24/65/1B-L/P-G5-16/550


Dimensional drawing




Product	D (max)	A (max)	B (max)	B (min)	C (max)
MASTER TL5 HO 24W/865 SLV/40	17 mm	549.0 mm	556.1 mm	553.7 mm	563.2 mm

TL5 HO 24W/865

Photometric data



Lightcolour /865



Lightcolour /865

MASTER TL5 High Output

Lifetime



LDLE_TL5-HO8_0001-Life expectancy diagram

LDLE_TL5-HO8_0002-Life expectancy diagram



LDLM_TL5-HO8_0001-Lumen maintenance diagram

