



MASTER TL-D 90 Graphica

MASTER TL-D 90 Graphica 36W/950 SLV/10

Low-pressure mercury discharge lamps with a tubular 26 mm envelope

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information		Operating and Electrical	
Cap base	G13 [Medium Bi-Pin Fluorescent]	Chromaticity coordinate Y (nom.)	360
Life to 10% failures (nom.)	6000 h	Lamp Luminous Efficacy EM (Nom)	65 lm/W
Life to 50% failures (nom.)	8000 h	Colour Rendering Index,horiz (Nom)	95
Life to 50% failures preheat (nom.)	10000 h	LLMF 2000 h Rated	93 %
LSF 2000 h Rated	99 %	LLMF 4000 h Rated	90 %
LSF 4000 h Rated	99 %	LLMF 6000 h Rated	88 %
LSF 6000 h Rated	99 %	LLMF 8000 h Rated	85 %
LSF 8000 h Rated	99 %	LLMF 12000 h Rated	82 %
LSF 12000 h Rated	89 %	LLMF 16000 h Rated	80 %
LSF 16000 h Rated	33 %	LLMF 20000 h Rated	78 %
LSF 20000 h Rated	2 %		
Light Technical		Temperature	
Colour Code	950 [CCT of 5,000 K]	Power (Rated) (Nom)	36.0 W
Lamp Luminous Flux 25°C EL (Nom)	2330 lm	Lamp current (nom.)	0.440 A
Lamp Luminous Flux (Nom)	2330 lm		
Colour Designation	Daylight		
Chromaticity coordinate X (nom.)	348		

MASTER TL-D 90 Graphica

Controls and Dimming

Dimmable	Yes
----------	-----

Approval and Application

Energy efficiency label (EEL)	B
Mercury (Hg) content (nom.)	2 mg
Energy consumption kWh/1,000 hours	43 kWh

Product Data

Full product code	871150088864825
-------------------	-----------------


Order product name	MASTER TL-D 90 Graphica 36W/950 SLV/10
EAN/UPC – product	8711500888648
Order code	928044795081
SAP numerator – quantity per pack	1
Numerator – packs per outer box	10
SAP material	928044795081
SAP net weight (piece)	135.000 g
ILCOS code	FD-36/53/1A-E-G13

Dimensional drawing

Product	D (max)	A (max)	B (max)	B (min)	C (max)
MASTER TL-D 90 Graphica 36W/950 SLV/10	28 mm	1199.4 mm	1206.5 mm	1204.1 mm	1213.6 mm

TL-D Graphica 36W/950

Photometric data





Lightcolour TL-D Graphica /950

Lightcolour TL-D Graphica /950


MASTER TL-D 90 Graphica

Lifetime



LDLE_TL-D9HCR_0002-Life expectancy diagram

LDLE_TL-D9HCR_0001-Life expectancy diagram



LDLM_TL-D9HCR_0001-Lumen maintenance diagram

